

◎ SPT030-080



Features

- ◎ Max. 24 rings with 3 A or max. 12 rings with 16 A
- ◎ Rings with 3 A or 16 A can be combined or 3A and 16A integrated together
- ◎ Outer diameter 80 mm
- ◎ Inner diameter max. 30 mm
- ◎ Fieldbus & Fast Ethernet support


Typical Applications

- Beverage Filling System
- Drain Inspection
- Food Processing
- Metrology System

Data

Number of rings:	Max. 12 rings with 16 A(P) / Max. 24 rings with 3 A(S)
circuits:	12*6A(p) / 24*3A(s)
Voltage:	500VAC@50Hz
Dielectric strength:	1500VAC@50Hz
Insulation resistance:	≥1000MΩ@500VDC
Wire Length:	Rotor/Stator:1000 mm
Rotation speed:	300 rpm
Protection class:	IP 54
Temperature:	-20 °C ~ +80 °C (-5 °F ~ +175 °F)
Housing material:	Aluminium
Inner Diameter (ID) :	Ø 30mm

Design Example-Power



Number of rings	2	3	4	6	9	12	18	24
Power(L*)	53.8	63.8	73.8	93.8	123.8	143.8	/	/

JINPAT Electronics CO. LTD
No.496 Huarong Road, Dalang St.,
Longhua District, Shenzhen, 518109, China.
Tel: +86-755-8204 2235
Email: sales@slipring.cn
www.slipring.cn

Order Information

Type of slip ring:

S	P	T	0	3	0	0	8	0
---	---	---	---	---	---	---	---	---

No. of rings with: max.3A

 voltage

 Standard max.24

 max.16A

 Standard max.12

Length of leads in mm: Rotor

 Standard: 1000 mm

 Stator

 Standard: 1000 mm

Inner diameter in mm:

--	--

 Standard: Ø 17mm